Summary Specification					
BIL. SEBUTHARGA/QUOTATION REF.:		<u>UBD/Q/260/2024 (Unidigital) - [T]</u>			
TARIKH DIIKLANKAN :	17 Disember 2024 [Selasa]				
TARIKH TUTUP :	31 Disember 2024 [Selasa]	JAM: 2 Petang			
	DOCUMENT	FEE:	B\$ 10.00		

IMPORTANT

The Official PDF quotation/tender form will be send via email once UBD Official receipt issued and send to vendors/supplier for confirmation of payment received.

Mode of Payments > REFER IN UBD WEBSITE

Please take note that the document fee for each of the New and Extended quotations will be BND 10.00 each

Important Note: Please ensure that you provide the correct details when making the payment.

 $Please\ email\ proof\ of\ the\ above\ payment\ to\ helpdesk.epay@ubd.edu.bn.\ ,\ finance@ubd.edu.bn, eprocurement.support@ubd.edu.bn.$

	TITLE: TO SUPPLY, DELIVER, INSTALL SMART TV AND SMART SCREEN CAST AT MAIN HALL, CHANCELLOR HALL, UBD	
No.	Quantity	Descriptions
1	8 units	65-inch Smart LED TV <u>Specifications:</u> refer the attachment
2	8 units	Portable TV Roller Stand <u>Specifications:</u> refer the attachment
3	1 lot	Smart Screen Cast 4K Split Screen 1 to 8 Specifications: refer the attachment

TITLE:		TO SUPPLY, DELIVER, INSTALL SMART TV AND SMART SCREEN CAST AT MAIN HALL, CHANCELLOR HALL	
No.	Quantity	Description	
1	8 Units	65-inch Smart LED TV • Tempered Smart 4K TV • Resolution Ratio 3840x2160 • Video display format: 1080p • DLED Straight down type • Support all format Video & Audio • HDMI Support • Power Input AC100-240-50/60HZ • Android System 9.0 • Support multiple languages • Support screencast • Support Wi-Fi connectivity • Model: 65 inch Tempered Smart 4K TV • Size of the LED: 65 inch • Resolution: 3840*2160 • LED back light: DLED straight down type • System: Android system 9.0 • Contrast: 4000:1 • Brightness: 270cd/m2 • The refresh rate: 60Hz • Run a memory: 4GB • The fuselage memory: 64GB • Network support: RJ45/WI-FiDouble Connection • HD HDMI interface: 1 • Computer VGA interface: 2 • Digital audio output: 1 • RF Antenna interface: 1 • Analog audio output (headset): 1 • USB multimedia interface: 2 • Power supply design: 1100-240V • Proportion of the screen: 16:9 • Video display format: 108W • The speaker: Two Stereo • Hanging Size 200x200mm • Optimum viewing distance: 2.8-3.5m • Main engine size: 1450*875*80mm	
2	8 Units	Portable TV Roller Srand VESA Compatible Portable Stand with Lockable Rollers 100KG Max Weight Rigid steel construction	

SMART SCREEN CAST 4K SPLIT SCREEN 1 TO 8 Wireless Transmitter (TX) x 2 UNITS 2. Wireless Receiver (RX) x 8 UNITS Factory Mode: E900 Plus Operating System: Linux Processors: Rockchip RK3566 CPU Parameters: A55 quad-core 1.8GHz Storage Configuration: 2GB + 16GB Video Output Interface: 1 HDMI 2.0 with a maximum resolution of 4K60 and supports 11 resolution settings Video Input Interface: 1*HDMI 1.4 with a maximum resolution of 1920x1080P60 Audio Output Interface: 1*3.5mm analog audio interface Ethernet LAN: Gigabit USB Host Interface: 2*TypeA, USB2.0, 1*TypeC USB.20 Power Interface: 12V/2A Split Screen (Maximum): 9 Simultaneous Connections: 64 Display Clarity: maximum 4K resolution for a single display, maximum 1080P resolution for each display in 2-4 screen displays, and maximum 720P resolution for each display in 5-9 screen displays Display Ratio: uniform, 16:9, 16:10, and 4:3 Video Decoding Capability: Supports H264 and H265, with a maximum resolution of 4K and maximum frame rate of 60 frames per second Audio Output Capability: 44.1KHz 16bit stereo sound, with both embedded HDMI audio output and 3.5mm analog audio output being able to output audio at the same time. Wifi Hotspot: WiFi6 2T2R Wifi Network Card: WiFi5 2T2R Protocol: 802.11ax, 802.11ac和802.11n Distance: 50m 3 1 Lot Wireless Frequency: Supports both 2.4GHz and 5GHz wireless signals, with the default frequency band set to 5GHz. Channel: It can be set to 20 channels in total, with 11 channels in the 2.4GHz frequency band and 9 channels in the 5GHz frequency band Screencast Delay: The average latency is less than 150ms Bridging: It supports both wireless and wired bridging Screen casting Source System: MAC, iOS, WIN, Android, and HarmonyOS Transmitter: USB transmitter, HDMI transmitter, and TYPEC transmitter Software Screen casting: WIN Sender Android Sender Airplay: The maximum resolution is 4K, and the maximum number of screen mirroring is 9 Wired Screen casting: The HDMI input can be looped out to HDMI output. Byom Application: Support USB camera feedback, USB microphone feedback, and USB speaker feedback Screen Touchback: Support USB Playback: Support loop playing of videos and images from USB flash drives • Screen casting Code: Support Mobile Screen casting Dedicated Display Mode: Four-screen display mode in landscape and portrait orientation on mobile devices Extended Desktop Screen casting: Support Automatic Full Screen: Support Startup standby screen replacement: Support

- Multi-screen Same Display: Wireless multi-screen display, wired multicast multi-screen display, and RTSP multi-screen display
- Web Settings: Built-in web back-end
- Control Software: WIN controller
- Host Mode: Android controller
- Power Consumption: The average power consumption shall not exceed 6 watts (excluding power supply for external USB cameras and other devices)
- Size: The dimensions are 180mm x 40mm x 110.9mm (excluding external adhesive rod
- Temperature Range: Operating temperature range: +5°C to +40°C Storage temperature range: -20°C to +60°C
- Humidity: Operating and storage relative humidity range: 0% to 90% (non-condensing)