

Summary Specification	
BIL. SEBUTHARGA/QUOTATION REF.:	<u>UBD/Q/285/2024 (Unidigital) - [G]</u>
TARIKH DIKLANKAN :	<u>04 Februari 2025 [Selasa]</u>
TARIKH TUTUP :	<u>18 Februari 2025 [Selasa]</u> JAM: 2 Petang
DOCUMENT FEE : B\$ 10.00	

IMPORTANT

The Official PDF quotation/tender form will be send via email once UBD Official receipt issued and send to vendors/supplier for confirmation of payment received.

Mode of Payments > REFER IN UBD WEBSITE

Please take note that the document fee for each of the New and Extended quotations will be BND 10.00 each

Important Note: Please ensure that you provide the correct details when making the payment.

Please email proof of the above payment to helpdesk.epay@ubd.edu.bn , finance@ubd.edu.bn,eprocurement.support@ubd.edu.bn.

TITLE :		TO PROVIDE AND INSTALL OMNIDIRECTIONAL BOUNDARY MICROPHONES FOR UBD CONFERENCE ROOM, ADMIN BUILDING.
No.	Quantity	Descriptions
1.	10 units	<p>BOUNDARY CONDESNER MICROPHONE</p> <p>To provide and install Boundary Condenser Microphone, 12" Cable, Omnidirectional, Black</p> <p>Cartridge Type: Electret Condenser Frequency Response: 70–16000 Hz Polar Pattern: Omnidirectional Cardioid Output Impedance: 180 Ω Sensitivity (at 1 kHz , open circuit voltage): -28 dBV/Pa(40 mV) Maximum SPL (1 kHz at 1% THD): 117 dB SPL Signal to Noise Ratio (referenced at 94 dB SPL): 74 dB Dynamic Range: 97 dB Self Noise (equivalent SPL, A-weighted, typical): 20 dB SPL Common Mode Rejection (10 Hz to 100 kHz): >45 dB Preamplifier Output Clipping Level (1% THD): -6 dBV Polarity: Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Power Requirements: 11–52 V DC, 2.0 mA</p> <p>Environmental Requirements Operating Temperature Range: -18 to 57 °C (0 to 135 °F)</p> <p>Relative Humidity: 0 to 95%</p> <p>*participating vendor specs to match polar pattern and frequency response as per image</p>

