

| Summary Specification           |  |
|---------------------------------|--|
| BIL. SEBUTHARGA/QUOTATION REF.: | <u>UBD/Q/201/2025 (CAMES) - [G]</u>            |
| TARIKH DIIKLANKAN :             | <u>04 November 2025 [Selasa]</u>               |
| TARIKH TUTUP :                  | <u>18 November 2025 [Selasa]</u> JAM: 2 Petang |
| DOCUMENT FEE : B\$ 10.00        |  |

### IMPORTANT

The Official PDF quotation/tender form will be send via email once UBD Official receipt issued and send to vendors/supplier for confirmation of payment received.

Mode of Payments > REFER IN UBD WEBSITE

Please take note that the document fee for each of the New and Extended quotations will be BND 10.00 each

**Important Note:** Please ensure that you provide the correct details when making the payment.

Please email proof of the above payment to [helpdesk.epay@ubd.edu.bn](mailto:helpdesk.epay@ubd.edu.bn) , [finance@ubd.edu.bn](mailto:finance@ubd.edu.bn),[eprocurement.support@ubd.edu.bn](mailto:eprocurement.support@ubd.edu.bn).

| TITLE : |          | <u>TO SUPPLY, DELIVER AND INSTALL LABORATORY BENCHTOP FOR CENTRE FOR ADVANCED MATERIAL AND ENERGY SCIENCES, UNIVERSITI BRUNEI DARUSSALAM</u>  |
|---------|----------|---|
| No.     | Quantity | SPECIFICATIONS  |
| 1       | 2 units  | <p><b>Laboratory Benchtop</b></p> <p>Specifications:</p> <ul style="list-style-type: none"> <li>- Steel Lab Wall Bench C Frame (2700 x 900 x 900) mm, Phenolic resin countertop: 12.7mm</li> <li>- Cabinet: 1.0mm full-thickness high-quality cold-roll steel sheet, steel surface is electrostatic powder coated with epoxy resin, the surface thickness of up to 1.15mm~1.2mm. the cabinet door is double-layered inside and outside, filled with sound insulation material.</li> <li>- Frame: 40*60*1.5mm thick high-quality cold-rolled rectangle tube, the steel surface electrostatic powder coated with epoxy resin.</li> <li>- Handle: Non-welded linear handle.</li> <li>- Rail: DTC 16-inch three-section silent rail.</li> <li>- Hinge: DTC 105'hinge.</li> <li>- Footing: Use laboratory-specific adjustable feet with an adjustment range of &gt;35mm, strong bearing capacity, the balance of the Lab bench can be adjusted.</li> </ul> |