

| Summary Specification | |
|---------------------------------|---|
| BIL. SEBUTHARGA/QUOTATION REF.: | UBD/Q/266/2025 (OAVC - RIS) - [T] |
| TARIKH DIIKLANAKAN : | 27 Januari 2026 [Selasa] |
| TARIKH TUTUP : | 10 Februari 2026 [Selasa] JAM: 2 Petang |
| DOCUMENT FEE : B\$ 10.00 | |

IMPORTANT

The Official PDF quotation/tender form will be send via email once UBD Official receipt issued and send to vendors/supplier for confirmation of payment received.

Please take note that the document fee for each of the New and Extended quotations will be BND 10.00 each

b) Quotations or tenders under Universiti Brunei Darussalam (Tabung UBD) can be identified by the letter [T] at the end of the quotation/tender reference number.

Example: UBD/Q/123/2023 – [T]

Please ensure that your company makes payment to the correct account:

For [T] references → Tabung Universiti Account

Account numbers and detailed payment steps are available on the Universiti Brunei Darussalam website under the section “Mode of Payment.”

Important Note: Please ensure that you provide the correct details when making the payment.

Please email proof of the above payment to helpdesk.epay@ubd.edu.bn, finance@ubd.edu.bn, eprocurement.support@ubd.edu.bn.

| TITLE : | | <u>TO SUPPLY, DELIVER, INSTALL, COMMISSION AND TEST AT SITE THE FOLLOWING ITEMS: 2 UNITS OF UV STERILIZATION STACKABLE INCUBATOR SHAKER, 1 UNIT OF A STACKABLE INCUBATOR SHAKER AND 1 UNIT OF A STAINLESS STEEL GRAVITY CONVECTION MICROBIOLOGICAL INCUBATOR , UNIVERSITI BRUNEI DARUSSLAM</u> |
|---------|----------|---|
| No. | Quantity | SPECIFICATIONS |
| 1. | 2 units | UV Sterilization Stackable Incubator Shaker <u>Specifications: -</u> - For large volume flask shaking culture of microorganism - 7-inch LCD touch operation screen, 2~300 rpm rotation speed depending on load and stacking, orbital shaking, 4-60oC temperature control range, 50 kg loading max, stackable up to 2 units, dimension (1330x820x700mm for 1 unit), UV sterilization, stainless steel, standard flask clamps |
| 2 | 1 unit | Stackable Incubator Shaker <u>Specifications: -</u> - For shaking culture of microorganism - LCD button control interface, 2~300 rpm rotation speed , 4-60oC temperature control range, 15 kg loading max, dimension (L550x W650 x H850 mm for 1 unit), UV sterilization, stainless steel, clamps (universal spring mesh, flask clamps, deep-well plate clamps, test tube holders, etc.) |
| 3 | 1 unit | Stainless steel Gravity Convection Microbiological Incubator <u>Specifications: -</u> Ideal for microbiological incubation and heated storage Maximum temperature 75oC, digital display, 2 shelves, single set point digital control, stainless steel interior, 75L capacity, outer dimension (565 x 530 x 720 mm) |