

Summary Specification	
BIL. SEBUTHARGA/QUOTATION REF.:	UBD/Q/211/2026 (FOS) - [T]
TARIKH DIKLANKAN :	<u>13 Oktober 2026 [Selasa]</u>
TARIKH TUTUP :	<u>27 Oktober 2026 [Selasa]</u> JAM: 2 Petang
DOCUMENT FEE :	B\$ 10.00

Important Note:

The Official PDF quotation/tender form will be send via email once UBD Official receipt issued and send to vendors/supplier for confirmation of payment received.

Please take note that the document fee for each of the New and Extended quotations will be BND 10.00 each

Payment Information

Quotations/tenders are identified as follows:

[T] – Tabung Universiti Brunei Darussalam Account

Please ensure payment is made to the correct account:

[T] → TABUNG UNIVERSITI BRUNEI DARUSSALAM

Payment details and account numbers are available under “Mode of Payment” on the UBD website

Note: Please ensure that you provide the correct details when making the payment.

Please email proof of the above payment to helpdesk.epay@ubd.edu.bn , finance@ubd.edu.bn ,
eprocurement.support@ubd.edu.bn.

TITLE :		TO SUPPLY, INSTALL AND DELIVER SPOTTING SCOPE, BINOCULAR, ACOUSTIC RECORDER, TRIPODS, TRAIL CAMERA & DIGISCOPING KIT TO FACULTY OF SCIENCE (ENVIRONMENTAL AND LIFE SCIENCES) UNIVERSITI BRUNEI DARUSSALAM
No.	Quantity	SPECIFICATIONS
1	1 unit	HD22-48x65 Spotting Scope (Angled Viewing) Including in the package Eyepiece Cap Objective Lens Cap Stay-On View-Through Carrying Case <i>Refer to the attachment for full specifications</i>
2	1 unit	12x50 HD Binoculars Vortex Vortex GlassPak Binocular Harness (Tan) Neck Strap Rainguard Eyepiece Cover 2 x Tethered Objective Lens Cover Lens Cloth <i>Refer to the attachment for full specifications</i>
3	2 units	Spec Ops Elite HP5 Ultra Trail Camera Trail camera is designed for reliable outdoor use, featuring a 2-inch color viewing screen for easy on-site setup and footage review, a fast adjustable 0.1–0.7 second trigger speed, and HDR night imaging with invisible IR illumination up to 100 feet. It captures 46 MP images and 1440p video with sound, supports Smart IR Video and up to 512 GB SDXC storage, and operates on 8 AA batteries, including alkaline, rechargeable, or lithium options, for extended field use. <i>Refer to the attachment for full specifications</i>
4	1 unit	Mini 2 (AA) Song Meter Acoustic Recorder A smaller, more lightweight and affordable Acoustic Recorder, which provides high quality recordings. It builds on the technology of the original series with a redesigned hinged lid and significantly improved battery life for the AA model thanks to an increased capacity of 8 batteries. It also features a 1/4" tripod mount for easy field deployment using off-the-shelf products. <i>Refer to the attachment for full specifications</i>

TITLE :		<u>TO SUPPLY, INSTALL AND DELIVER SPOTTING SCOPE, BINOCULAR, ACOUSTIC RECORDER, TRIPODS, TRAIL CAMERA & DIGISCOPING KIT TO FACULTY OF SCIENCE (ENVIRONMENTAL AND LIFE SCIENCES) UNIVERSITI BRUNEI DARUSSALAM</u>
No.	Quantity	SPECIFICATIONS
5	1 unit	TR-13 Travel Tripod with Dual-Action Ball Head (62.5") Included in the package STA-100B Smartphone Tripode Adapter <i>Refer to the attachment for full specifications</i>
6	1 unit	DX 3-Axis Smartphone Digiscoping Kit Included in the package Olight Imini 2 Rechargeable Key Ring Flashlight (Black) <i>Refer to the attachment for full specifications</i>

To Supply, Install and Deliver Spotting Scope, Binocular, Acoustic Recorder, Tripods, Trail Camera & Digiscoping Kit to Faculty of Science (Environmental and Life Sciences) Universiti Brunei Darussalam - NEW REQUEST

No	Description	Quantity
1	HD22-48x65 Spotting Scope (Angled Viewing) Including in the package Eyepiece Cap Objective Lens Cap Stay-On View-Through Carrying Case Optics 45 degree angled-viewing HD 22-48x65 Spotting Scope is engineered with superior glass and specialized optical coatings to provide clear and bright images at all magnification. The triplet apochromatic lens configuration is made of high-density (HD) extra-low dispersion (ED) glass to increase light transmission, minimize distortion, and virtually eliminate chromatic aberration. All air-to-glass surfaces have Vortex's XRPlus anti-reflective coatings to minimize light loss and maximize image brightness, while the Porro prisms have highly reflective dielectric coatings that improve brightness, clarity and color accuracy. Performance Viewing Angle: Angled Magnification: 22 to 48x Objective Lens Diameter: 65 mm Field of View 22x: 138.0' @ 1000 yd / 46.0 m @ 1000 m 48x: 84.0' @ 1000 yd / 28.0 m @ 1000 m Minimum Focus Distance 26.2' / 8.0 m 22x: 3 mm Exit Pupil Diameter 48x: 1.4 mm Eye Relief 17.0 to 16.7 mm Use and Handling Angled viewing Eyepiece is set at a 45° angle to optical tube for comfortable viewing when standing, sitting, or lying prone Helical focusing collar allows for fast, fine adjustments 3-1.4mm exit pupil Twist-up rubber eyecup for easy use with or without eyewear 17-16.7 mm eye relief Rotating tripod ring allows rotation of the eyepiece to a sideways position, providing adjustable viewing angles 1/4"-20 tripod mount Features Fogproof Yes: Argon Filled Environmental Resistance Water-Resistant (Unrated) General Tripod Mounting Thread 1/4"-20 Female Dimensions L: 14.8" / L: 37.6 cm Weight 3.6 lb / 1.6 kg	1 unit

2	12x50 HD Binoculars Vortex Vortex GlassPak Binocular Harness (Tan) Neck Strap Rainguard Eyepiece Cover 2 x Tethered Objective Lens Cover Lens Cloth Powerful magnification and a generous objective lens for a bright view even in low light conditions, the 12x50. A versatile optic suited to a wide range of uses. They can be mounted on a tripod with a separately sold adapter, and come with a Vortex GlassPak harness for comfortable use during hours of observation. Prism Type: Roof Performance Magnification: 12x Objective Lens Diameter: 50 mm Angle of View: 5.2° (Actual) Field of View: 271' @ 1000 yd / 89.97 m @ 1000 m Minimum Focus Distance: 6' / 1.83 m Exit Pupil Diameter: 4.2 mm Eye Relief: 14 mm Interpupillary Adjustment: 60 to 75 mm / 2.4 to 3" Diopter Adjustment: Yes Focus Type: Center Use and Handling Short-hinge bridge cuts weight and exposes more surface for handling Adjustable interpupillary distance: 60-75mm Oversized knurled center focusing wheel Textured diopter ring on right eyepiece Twist-up, soft-tapered rubber eyecups Construction Details GlassPak binoculars harness with zippered accessory pocket Protective rubber armor provides a slip-resistant grip O-ring sealed and argon filled to be IPX7 waterproof and resistant to internal fogging when moving through extreme temperature and environmental conditions Scratch-resistant ArmorTek exterior lens coatings repel oils and corrosive materials from lenses General Dimensions: 6.4 x 5.3" / 16.26 x 13.46 cm Weight: 28.9 oz / 819 g	1 unit
---	---	--------

3	Spec Ops Elite HP5 Ultra Trail Camera Trail camera is designed for reliable outdoor use, featuring a 2-inch color viewing screen for easy on-site setup and footage review, a fast adjustable 0.1–0.7 second trigger speed, and HDR night imaging with invisible IR illumination up to 100 feet. It captures 46 MP images and 1440p video with sound, supports Smart IR Video and up to 512 GB SDXC storage, and operates on 8 AA batteries, including alkaline, rechargeable, or lithium options, for extended field use. Image & Video Quality 46 MP Image Capability 1440p Full HD Videos with Sound (5 sec. - 2 min.) HDR Night Images (High Dynamic Range) H.264 Video Format Display & User Interface 2-Inch Color Viewing Screen Multilingual Programming Menu Nighttime Performance Invisible “Night Vision” Infrared LED Illumination Adjustable IR Flash (Power Save, Fast Motion, Long Range) 100 Ft. IR Flash Range New "RADIANT 5" Night Illumination Technology Illuma-Smart Technology (Auto-adjusts IR Flash for Optimal Night Photos) Trigger & Detection Adjustable 0.1 - 0.7 Second Trigger Speed 0.5 Second Recovery Time Adjustable Detection Range up to 80 ft. Shooting Modes & Customization Timelapse Plus Camera Mode with Infrared-Triggered Photos Smart IR Video Up to 8 Multi-Shot Images Up to 8 Rapid Fire Images Programmable Picture Delay (1 sec. – 60 min.) Selectable Start / Stop Image Timer Storage & Power Supports up to 512GB SDXC Memory Card (Not Included) SD Card Management Options Long Battery Life (8 AA Batteries, Not Included) Battery Meter Compatible with Alkaline, Rechargeable, and Lithium Batteries 12-Volt External Power Jack Additional Features Picture Info Bar Displays: Time, Date, Temperature, Moon Phase, Barometric Pressure, Camera ID Compact Case Size: 5" x 3.5" x 2" ¼" -20 Tripod Socket Metal Tree Mount Bracket Compatible with Browning Buck Watch Timelapse Viewer Software	2 units
---	---	---------

4	Mini 2 (AA) Song Meter Acoustic Recorder A smaller, more lightweight and affordable Acoustic Recorder, which provides high quality recordings. It builds on the technology of the original series with a redesigned hinged lid and significantly improved battery life for the AA model thanks to an increased capacity of 8 batteries. It also features a 1/4" tripod mount for easy field deployment using off-the-shelf products. This is a simple, yet innovative device for recording birds, frogs and other species that communicate vocally. It is weatherproof, robust and is easily mountable using screws, rope or cables such as the Python Lock. The recorder comes complete with a field serviceable microphone for high-quality recordings and a second microphone (available separately) can be added for stereo recordings. Recording Format: 16-bit WAV Recording Channels: One (two with second microphone added) The recorder supports the following sample rates in samples per second on one or two channels: 8000, 12000, 16000, 22050, 24000, 32000, 44100, 48000, 96000 Built-in-Microphone Directional Characterisitc: Omni-Directional Programming Method: iOS or Android app using Bluetooth Quick Start Schedule: Yes Advanced Schedule: (different each day) – Yes Adjustable Gain: Yes High Pass Filter: 2-pole at 100 Hz Battery Type: 4 or 8 AA batteries Battery Life: up to 530 hours (using low-power mode at 24kHz mono) Storage Memory Storage: 1 SDHC/SDXC flash card slots (Class 4 or greater); Supports up to 2TB SDXC cards Dimensions • Height: 4.7" / 120 mm • Width: 7.0" / 177 mm • Depth: 1.6" / 40 mm Weight • Without batteries: 0.54 lb / 245g • With 8 AA batteries: 0.95 lb / 429g Weatherproof: Fully weatherproof with integrated humidity controls Integrated Mounting Bracket: Yes (supports many mounting options) Operating Temperature: -4°F to +185°F or -20°C to 85°C	1 unit
---	---	--------

5	TR-13 Travel Tripod with Dual-Action Ball Head (62.5") Included in the package STA-100B Smartphone Tripode Adapter Travel Tripod with Dual-Action Ball Head that includes Arca-type-compatible quick release plate, and the head has a separate locking knob for the ball, and one for the 360° pan. The cut notch on the side of the ball head allows you to place a camera at a 90° angle, and the head can support point-and-shoot, mirrorless, and DSLR cameras weighing up to 13.2 lb. The four-section aluminum legs have flip locks that open so you can extend them along with the rapid center column to a maximum height of 62.5". To get to the minimum height of 16.5", the legs splay completely out, and they have three variable angles with independent leg spread to adjust when shooting on uneven terrain. The tripod's center column is reversible to get closer to the ground. The legs fold in the reverse to a compact 18.2" to be compact for travel, and rubber feet prevent the tripod from sliding on smooth surfaces. Head Camera Mounting: 1/4"-20 Screw (Quick Release Plate: Arca-Type) Head Type: Ball Head Base Mount: Flat Base with 3/8"-16 Female Pan & Tilt Drag Control: No Independent Pan Lock: Yes Vertical Tilt: +90° to 0° Legs Primary Material: Aluminum Leg Lock: Flip Lock Leg Sections: 4 Independent Leg Spread: Yes Leg Positions: 3 Positions General Load Capacity: 13.2 lb / 5.99 kg Maximum Working Height: 62.5" / 158.8 cm Center Column: Yes (Round): Removable, Reversible Max Height with Center Column Down: 53.1" / 134.87 cm Minimum Working Height: 16.5" / 41.9 cm Closed Length: 18.2" / 46.2 cm Bubble Level: Yes Weight: 2.9 lb / 1.32 kg	1 unit
---	--	--------

6	DX 3-Axis Smartphone Digiscoping Kit Included in the package Olight Imini 2 Rechargeable Key Ring Flashlight (Black) Smartphone Digiscoping Kit to be used on spotting scopes, binoculars, and telescope eyepieces—including standard 1.25" and larger 2" telescope eyepieces. Celestron includes two rings that allow the adapter to be mounted on smaller optics, such as microscopes. Included with the kit is a remote shutter release that can be used on virtually any iOS or Android smartphone. Dimensions: 6.5 x 5.5 x 4.25" / 165.1 x 139.7 x 108.0 mm Weight: 10.0 oz / 283.0 g For Telescopes, Binoculars & Spotters Take Stills and Video through Eyepiece Bluetooth Remote for iOS & Android Remote Eliminates Unwanted Vibrations Microscope and Smaller Optic Adapters Fits Eyepiece Diameters from 25 to 60mm Fits Phones from 2.6 to 3.5" Wide Easy Spring-Clamp Installation with Lock Compatible with a Wide Variety of Phones Aluminum Frame and Polymer Body	1 unit
----------	---	---------------

7	3-Way Live Advanced Tripod Included in the package 3-Way Live Advanced Tripod 200PL-PRO Quick Release Plate Carry Bag Tripod made for a hybrid photo-video head ideally suited for travel photography and videography. Paired with the Advanced Travel Aluminum Tripod, the 3-way fluid head provides foldable handles for compactness, and a fluid drag system on pan and tilt axes ensures camera movements are smooth, controlled, and precise. A dedicated quick release plate provides excellent camera stability for all shooting positions, and this unique plate system has the added benefit of being compatible with Manfrotto 501PL and Arca-type tripod plates. The tripod legs are made of sturdy aluminum alloy, and together with the head reach a maximum height of 59.5". Each leg is composed of four sections, which can be adjusted and securely locked into place with the lever locks found on all segments, and a side-pull selector enables quick setup with both hands. An Easy Link attachment at the top portion of the leg section allows you to attach external accessories, and rubberized feet avoid skidding and help keep the tripod stable on uneven terrain. An integrated hook is also included so you can add a weight and increase the stability of your tripod when shooting in more difficult conditions. Camera Mounting: 1/4"-20 Screw (Quick Release Plate: 200PL / 501PL / Arca-Type) Head Type: Fluid Head Base Mount: Flat Base with 3/8"-16 Female Pan & Tilt Drag Control: No Independent Pan Lock: Yes Independent Tilt Lock: Yes Vertical Tilt: +90° to -45° Lateral Tilt: -80° to +90° Legs Primary Material: Aluminum Leg Lock: Flip Lock Leg Sections: 4 Independent Leg Spread: Yes Leg Positions: 3 Positions General Load Capacity: 13.23 lb / 6 kg Maximum Working Height: 59.4" / 151 cm Center Column: Yes (Faceted): Ballast Hook Max Height with Center Column Down: 51.97" / 132 cm Minimum Working Height: 16.5" / 42 cm Closed Length: 15.7" / 40 cm Bubble Level: Yes Weight: 4.34 lb / 1.97 kg	1 unit
---	--	--------